

# FIRE WALL PANEL A-60

## PRODUCT OVERVIEW



### Safety & Construction

- > Panel, tongue and glue made of high-temperature resistant materials.
- > Seamless panel surface is ready for painting, lamination or wall paper decoration.

### Services

- > Wall panels are stackable and delivered on pallets.
- > Wall panels can be cut to size for faster installation.
- > Worldwide supply.

### Documentation

- > Certificates (DNV Module B & D, SDoC, DoC)
- > Installation guide.

# FIRE WALL PANEL A-60



- ① Wall panel
- ② Tongue
- ③ Glue connection
- ④ Profile\*

\*not provided by KAEFER

## Technical details

Fire properties: Class A-60 bulkhead

System connection: Tongue and glue

## Size range

Length: 2.300 mm +/- 3 mm

Width: 600 mm +/- 3 mm

Thickness: 50 mm +/- 3 mm

## Physical properties

Panel system weight: c. 23 kg/m<sup>2</sup>

Airborne sound level (RW): 34 dB

## Certification

Module B: MEDB00002Y9

Module D: MEDD00000DN

Fire Safety Products from KAEFER are used on more than 600 vessels (cruise ships, mega yachts, ferries).

All products complies the Hong Kong International Convention requirements.



## Contact

KAEFER Schiffsausbau GmbH  
Getreidestr. 3  
28217 Bremen

Mr. Jan-Timo Kolthammer  
+49 421 6109 199  
firedoors@kaefer.com

If you have any further questions, do not hesitate to contact us.



www.kaefer.com



Product video